

DATA SHEET

Dual DVI-D Adapter For Q43/Q45-Mainboards D2833-A / D2833-B

Issue June 2009
Product Dual DVI-D Adpt. D2833

Pages 1

This dual DVI-D extension adapter provides two single-link DVI-ports for your mainboard

Physical specifications

PCIe card with ATX or Low Profile connector bracket.

Interface

PCIe x16 slot required

Supported mainboards / chipsets

D2811 (iQ43)
D2812 (iQ45)
D2831-S / D2836-S (iQ45)

Display modes

VGA	640 x 480	60Hz
SVGA	800 x 600	60Hz
XGA	1024 x 768	60Hz
SXGA	1280 x 1024	60Hz
SXGA	1280 x 1024	60Hz
UXGA	1600 x 1200	60Hz
"Wide"	1440 x 900	60Hz
	1680 x 1050	60Hz
	1920 x 1200	60Hz

Note: Additional display resolutions possible - dependent on attached DVI monitor

Operating systems

Microsoft Windows® XP
Microsoft Windows® Vista®
(no drivers required)

Package content

D2833-A: DVI-D adapter with SFF slot bracket incl.
DVI-cable *CFO:E003-R150-RS* for second port

D2833-B: DVI-D adapter with fullsize ATX slot bracket incl.
DVI-cable *CFO:E003-R150-RS* for second port

Note: This DVI adapter requires BIOS support that may not be a provided by non-FTS mainboards.



Information about environmental care, policies, programs and our Environmental Guideline FSC 03230:

ts.fujitsu.com/aboutus

Take back and Recycling information: ts.fujitsu.com/recycling

All rights reserved, including intellectual property rights. Technical data subject to modifications and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see: ts.fujitsu.com/terms_of_use.html
Copyright © Fujitsu Technology Solutions GmbH 2009

Published by:
Fujitsu Technology Solutions GmbH
de.ts.fujitsu.com