

Data Sheet FUJITSU Mainboard D3402-B µATX

Extended Lifecycle Series





Designed for 24/7 continuous operation

Chipset:

Intel® Q170 Express Chipset

Processors:


Intel® Core $^{\text{m}}$ i7 / i5 / i3 – (6 $^{\text{th}}$ gen.) processor series Intel® Pentium® / Future Celeron® processor series Socket LGA1151 – up to 65W TDP

Memory:

DDR4 2133 SDRAM (UDIMM)

Product Features:

Intel® iAMT 11.0 / vPro 2015
Onboard Support for M.2 SSD (PCIe or SATA)
Intel® HD Graphics
PCI Express Gen3
Multichannel Audio & Intel GbE LAN onboard
USB 2.0/3.0 and USB 3.0 Socket (Stick) onboard
Trusted Platform Module V2.0 (Infineon) onboard
HW Watchdog onboard









































Page 1 of 4 ts.fujitsu.com/mainboards

Features and benefits

Board Size reduced μ ATX: 9.6" x 8.4" (243.8 x 213.4 mm)

Chipset Intel® Q170 Express Chipset

Memory

4 DIMM Sockets DDR4, max. 64GB, Dual Channel, 2133MHz (CL15), UDIMM, 1.2V/2.5V, 288-pin, non-ECC.

Effective memory speed depends on installed processor

Processor

Intel® Core™ i7 / i5 / i3 – (6th generation) processor series Intel® Pentium® / Future Celeron® processor series

Socket LGA1151, max. 65W TDP

(For details on supported processors please refer to OEM FTP Server)

Power Specification

ATX- 24 Pin or ATX- 20 Pin + 4 Pin (12V) Power Connector required Support for Soft-Off Power Supplies 12V and 3.3V Supply Voltage on PCle Slots

3.3V Auxiliary Supply Voltage on PCIe Slots (Wake-Up Function) On board CPU Voltage Regulator, 5V / 2A Auxiliary Power required for USB Wake-Up from Save-to-RAM, Save-to-Disk

Power Supply Requirements

for onboard components (worst case incl. processor & memory; w/o USB devices; w/o PCle cards, w/o M.2 / SATA drives)

Source	Voltage	Min. PS Load	Max.Voltage Tolerance	Mainboard Capacitive Load	Max. Mainboard Current
	+ 12V	0.05A	± 5 %	5.000µF	8A/12A 1)
Main Power	- 12V	0A	± 10 %	470µF	0.3A
Supply	+ 5V	0.2A	± 5 %	3.000µF	6.0A
	+ 3.3V	0A	± 5 %	3.000µF	0.5A
Aux. Power	+ 5Vaux	0A	+5 % / -3%	3.000µF	2.5A

1) Max. Cont. Current = 8A; max. Surge Current = 10A (< 100sec) / 12A (< 10ms)

BIOS

AMI Aptio 5.x (UEFI) BIOS

modified and adapted by Fujitsu Technology Solutions; Recovery BIOS, SM-BIOS (DMI), BIOS and CPU Microcode Update, Quick Boot, Logo Boot, Quiet Boot, Plug & Play, Automatic DRAM and PCIe Configuration, BIOS Support for S.M.A.R.T., Advanced Power Management, ACPI S3/S4, Wake on time from S5. Boot support for M.2 SSD (PCIe-based or SATA-based modules, AHCI)

Security Features

Recovery BIOS, System and BIOS Password, Boot Sequence Control, Serial-/ Parallel-/ USB- Port Access, Boot Sector Virus Warning, Write Protection for Flash BIOS, EraseDisk (optional BIOS Feature)

Trusted Platform Module (Infineon SLB 9665; TPM V2.0; TCG compliant)

Special Features

Silent Fan Independent temperature related processor fan and

system fan supervision and control

View and adjust Silent Fan features System Guard

Noise reduction for optical and hard disk drives Silent Drives

Recovery BIOS Restores a corrupted BIOS

Simple driver update with Driver&Utilities DVD Desk Update Multi Boot Comfortable boot from any boot device

HDD Password Access protection for disk drives

CSA / UL certified CSA 60950-1-07 SE / UL 60950-1 SE (planned)

Supported / Released Operating Systems

OS	"Runnable"	"Tested/Released by Fujitsu"
MS Windows XP	-	
MS Windows 7-32	Χ	X
MS Windows 7-64	X	X
MS Windows 8.1-64	Χ	X
MS Windows 10-64	X	X
Linux-32	Х	tbd
Linux-64	Χ	tbd

Designed for 24 / 7 use

Longlife components for 24 / 7 continuous operation @ 50°C Revision control & Extended Lifecycle (up to 3 years)

Graphics

Intel® HD Graphics (depends on installed processor), DX12

Audio

Realtek ALC671, 5.1-channel, High Definition Audio Codec

Intel Jacksonville i219LM with 10/100/1000 MBit/s, iAMT 11 / vPro Support, Wake-on-LAN (WoL) by interesting Packets, Link Status Change and Magic Packet™, PXE Support, BIOS MAC Address Display

Drives

5 x Serial ATA III 600 Interface (up to 6GBit/s, NCQ, AHCI, RAID 0/1/5/10) 1 x M.2 Socket (2260/2280) for PCIe (4 lanes) or SATA based M.2 modules, AHCI Boot support

Features	D3402-B
Chipset	iQ170
Board Size	reduced µATX
VGA ¹⁾ / DVI-I / DVI-D / DP V1.2 / 2 nd DP V1.2 / LVDS	- - \ \ \ - -
Stereo Audio / 5.1 Multichannel Audio	-/✓
Buzzer / int. Speaker Support	-/✓
LAN Gbit / 100 Mbit / 10 Mbit / WoL / LAN Boot	√ √ √ √ √
iAMT 11.0 vPro / iAMT Standard / DASH V1.0	√ - √
SATA / ATA / RAID / eSATA-support / M.2 (PCIe x4 or SATA)	√ - √ √ √
FireWire™ / USB 2.0 / USB 3.0	- √ √
FAN monitored & controlled PSU ²⁾ / CPU / AUX1 / AUX2	√ √ √ √
TEMP monitored CPU / onboard sensors / external sensor	√ √ -
Special Features	
Silent Fan / Silent Fan LT / System Guard / Silent Drives	√ - √ √
Recovery BIOS / Desk Update / Multi Boot	√ √ √
HDD Password / HDD Encryption / EraseDisk ³⁾ / TPM	√ - √ √
BIOS POST Watchdog / BIOS Boot Watchdog / OS HW Watchdog	-1-1 ✓
Logo Boot Option / Intel On Screen Branding	√ √
High Efficiency Core Voltage Regulator Design	✓
Operating Mode 24-7 / 8-5 (hrs per day - days per week)	√ -
Mainboard operating temperature range (chassis inside)	10°C − 50°C
ILM - Backplate / ILM + Heatsink combined 5)	√ -
Internal Connectors	
DIMM Sockets (DDR4-2133)	4
PCI Express x16 Slot (Gen3)	1
PCI Express x16 Slot (4 Lanes, Gen3) / x1 Slot (Gen3)	1/2
PCI Slots (32Bit, 33 MHz, Rev. 2.3)	-
SATA-600 / SATA-300 / ATA / Floppy / M.2 SSD	5/-/-/-/1
S/PDIF (digital Audio) OUT / IN	-/-
Frontpanel Audio (9-Pin, HD Audio)	1
USB 2.0 channels / USB 3.0 channels / USB Stick (3.0)	4/2/1
Serial (COM2, RS232)	1
FAN PSU ²⁾ / CPU / AUX1 / AUX2	1/1/1/1
SMBus (Case Temperature)	-
Intrusion (Case Open)	1
Parallel Port Pin Connector ⁴⁾	1
ATX Power Supply (24 pin + 4 pin) / 12V-only Power Supply	√ -
External Connectors	
VGA Sub D 1) / DVI-I / DVI-D / DisplayPort V1.2	-/-/1/2
Audio Mic. In / Line in / Line out (or driver configuration)	1/1/1
LAN (RJ-45)	1
PS/2 Mouse / Keyboard	1 / 1
USB 2.0 / USB 3.0	2/4
Serial (COM1, RS232)	1
Parallel (EPP/ECP) 4)	-


- VGA possible via optional converter board D3453 or DP-VGA-converter (dongle)
- Not supported by standard Power Supplies Optional BIOS Feature, License required
- External parallel port possible via optional connector cable Note: Intel limitation

 LPC-DMA-Mode no longer supported


Combined Backplate: Can not be used for pushpin Heatsin

Page 2 of 4 ts.fuiitsu.com/mainboards

External Connectors



Connector / Socket Diagram



Further industrial products offered by Fujitsu

- Connectors
- KVM Switches
- Relays
- Touch Panels
- Thermal Printers
- Wireless Modules





24 Volt Kiosk Printers



Multi-Input Touch Panels

Contact:

Fujitsu Components Europe, B.V. Tel.: +31 (0)23 556 0910

Fax: +31 (0)23 556 0950

Website: emea.fujitsu.com/components

Address: Diamantlaan 25 2132 WV Hoofddorp Netherlands

More information

Fujitsu products, solutions & services

Products

www.fujitsu.com/global/products/ In addition to the Fujitsu [Product name], Fujitsu offers a full portfolio of other computing products.

Computing products

- Storage systems: ETERNUS
- Server: PRIMERGY, PRIMEQUEST, Fujitsu SPARC M10, BS2000/OSD Mainframe
- Client Computing Devices: LIFEBOOK, STYLISTIC, ESPRIMO, FUTRO, CELSIUS
- Peripherals: Fujitsu Displays, Accessories
- Software
- Network

Product Support Services with different service levels agreements are recommended to safeguard each product and ensure smooth IT operation.

Solutions

http://www.fujitsu.com/global/solutions The Fujitsu solutions combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu's Solutions include parts of one or more activity groups (e.g., planning, implementation, support, management, and training services) and are designed to solve a specific business need.

Infrastructure Solutions are customer offerings created by bringing Fujitsu's best products, services and technologies together with those from partners to deliver benefit to our customers' businesses.

Industry Solutions are tailored to meet the needs of specific verticals.

Business and Technology Solutions provide a variety of technologies developed to tackle specific business issues such as security and sustainability, across many verticals.

Services

www.fujitsu.com/global/services/
Several customizable Fujitsu Service
offerings ensure that IT makes a real
difference and delivers true business value.
We do this by leveraging our extensive
experience in managing large, complex,
transformational IT programs to help clients
in planning, delivering and operating IT
services in a challenging and changing
business environment.

Application Services support the development, integration, testing, deployment and on-going management of both custom developed and packaged applications. The services focus on delivering business and productivity improvements for organizations.

Business Services respond to the challenge of planning, delivering and operating IT in a complex and changing IT environment.

Managed Infrastructure Services enable customers to deliver the optimal IT environment to meet their needs – achieving high levels of IT service quality

Fujitsu green policy innovation

user environments.

www.fujitsu.com/global/about/environment/ Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to resolve issues of environmental energy efficiency through IT. Please find further information at:

and performance for data center and end



More information

Learn more about Fujitsu, please contact your Fujitsu sales representative, Fujitsu business partner, or visit our website. www.fujitsu.com/fts/mainboards/

Copyright

© 2015 Fujitsu Technology Solutions GmbH Fujitsu and the Fujitsu logo are trademarks or registered trademarks of Fujitsu Limited in Japan and other countries.

Intel Chipset Q170 and Intel Core i7 / i5 / i3 are trademarks or registered trademarks of Intel Corporation in America and other countries. Other company, product and service names may be trademarks or registered trademarks of their respective owners.

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.

Disclaimer

Technical data subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

Fujitsu Technology Solutions GmbH OEM Mainboard Sales Email: <u>oem-sales@ts.fujitsu.com</u>

Website: http://ts.fujitsu.com

Page 4 of 4 ts.fujitsu.com/mainboards