

Data Sheet

FUJITSU Mainboard D3434-S Mini-ITX

Industrial Series

Available from
04/2016



Powered by the Intel® H110 Express Chipset supporting DDR4 2133 SDRAM Memory and 6th generation Intel® Core™ i3 / i5 / i7 Processors (Socket LGA1151)
Designed & approved for enhanced operating temperature range from 0°C to 60°C
Designed & approved for 24/7 continuous operation

Chipset:

Intel® H110 Express Chipset

Processors:


Intel® Core™ i7 / i5 / i3 – (6th gen.) processor series
Intel® Pentium® / Intel® Celeron® processor series
Socket LGA1151 – up to 65W TDP

Memory:

DDR4 2133 SDRAM (SO-UDIMM)

Product Features:


Intel® HD Graphics (integrated in processor e.g. HD510/530)
DVI-D, DP V1.2, eDP and Dual Channel LVDS support
PCI Express x16 Gen3 and Mini-PCI Express onboard
8 Bit GPIO & multichannel Audio onboard
Onboard support for M.2 SSD (SATA-based M.2)
USB 2.0 and USB3.0 onboard
2 x Intel GbE LAN onboard (incl. teaming support)
Intel integrated TPM V2.0 onboard



Dual Power Supply (ATX compliant & 12V only)
BIOS-POST/-Boot & OS – HW Watchdog onboard



(planned)



Features and benefits

Board Size Mini-ITX: 6.7" x 6.7" (170 x 170 mm)

Chipset Intel® H110 Express Chipset

Memory

2 x SO DIMM Socket DDR4, max. 32GB, Dual Channel, 2133MHz (CL15), UDIMM, 1.2V, 256-pin, non-ECC.

Effective memory speed depends on installed processor

Processor

Intel® Core™ i7 / i5 / i3 – (6th generation) processor series

Intel® Pentium® / Intel Celeron® processor series

Socket LGA1151, max. 65W TDP

(For details on supported processors please refer to OEM FTP Server)

Power Specification

ATX- 24 Pin / ATX- 20 Pin or 12V only Power Supply required; Support for Soft-Off Power Supplies; 3.3V Auxiliary Supply Voltage on PCIe Slot (Wake-Up Function)

Power Supply Requirements

for onboard components (worst case incl. processor & memory; w/o USB devices; w/o PCIe cards, w/o M.2, w/o SATA drives)

Source ¹⁾	Voltage	Min. PS Load	Max.Voltage Tolerance	Mainboard Capacitive Load	Max. Mainboard Current
ATX Power Supply	+ 12V	0.05A	± 5 %	1.300µF	8A/12A ²⁾
	- 12V	0A		--	not used
	+ 5V	0.2A	± 5 %	900µF	3A
	+ 3.3V	0A	± 5 %	350µF	0.5A
	+ 5Vaux	0A	+5 % / -3%	330µF	0.5A
12V only PSU	+12V	0A	± 5 %	1.300µF	8A/12A ²⁾

1) ATX PSU or 12V only DC Supply

2) Max. Cont. Current = 8A; max. Surge Current = 10A (< 100sec) / 12A (< 10ms)

BIOS

AMI Aptio 5.x (UEFI) BIOS

modified and adapted by Fujitsu Technology Solutions; Recovery BIOS, SM-BIOS (DMI), BIOS and CPU Microcode Update, Quick Boot, Logo Boot, Quiet Boot, Plug & Play, Automatic DRAM and PCIe Configuration, BIOS Support for S.M.A.R.T., Advanced Power Management, ACPI S3/S4, Wake on time from S5.

Boot support for M.2 SSD (SATA-based M.2, AHCI / NVME)

BIOS integrated HW Diagnostic Tool, Watchdog Support

Security Features

Recovery BIOS, System and BIOS Password, Boot Sequence Control, Serial- / USB-Port Access Protection, Boot Sector Virus Warning, Write Protection for Flash BIOS, EraseDisk (BIOS Feature), Intel integrated TPM V2.0

Special Features

Silent Fan	Independent temperature related processor fan and system fan supervision and control
System Guard	View and adjust Silent Fan features
Silent Drives	Noise reduction for optical and hard disk drives
Recovery BIOS	Restores a corrupted BIOS
Desk Update	Simple driver update with Driver & Utilities DVD
Multi Boot	Comfortable boot from any boot device
HDD Password	Access protection for disk drives
Always On	Reliable power-on whenever voltage is connected
Never Off	Option to prevent the system from being shut down
CSA / UL / FCC certified	cCSAus 60950-1/ FCC-B (planned)

Supported / Released Operating Systems

OS	"Runnable"	"Tested/Released by Fujitsu"
MS Windows XP	--	--
MS Windows 7-32/64	X	X
MS Windows 8.1-64	X	X
MS Windows 10-64	X	X
Linux-32/64	X	--

Designed for Industrial Applications

Longlife components Designed for 24/7 use in industrial applications

Revision control Strict control and pre-announcement

Extended lifecycle Mainboard available for more than four years

Industrial grade EMI immunity

Enhanced operating temperature range (0°C-60°C) ¹⁾

Graphics

Intel® HD Graphics, DX12, Embedded Display Port (2 lanes supported)

DVI-D, 1 x DisplayPort V1.2, Dual-Channel 24bit LVDS (max. 2 indep. displays)

Audio

Realtek ALC671, 5.1-channel, High Definition Audio Codec

LAN

Intel i219LM & i210AT with 10/100/1000 MBit/s,

Wake-on-LAN (WoL) by interesting Packets, Link Status Change and

Magic Packet™, PXE Support, BIOS MAC Address Display, Teaming Support

Drives

2 Serial ATA III 600 Interface (up to 6Gbit/s), NCQ, AHCI;

1 x M.2 Socket (2242/2260) for SATA based M.2 modules, AHCI Boot support

Features	D3434-S
Chipset	iH110
Board Size	Mini-ITX
VGA / DVI-I / DVI-D / DP V1.2 / 2 nd DP V1.2 / LVDS / eDP	- / - / ✓ / ✓ / - / ✓ / ✓
Buzzer / int. Speaker Support / 5.1 Multichannel Audio	✓ / ✓ / ✓
Dual LAN Gbit / 100 Mbit / 10 Mbit / WoL / LAN Boot	✓ / ✓ / ✓ / ✓ / ✓
iAMT 11.0 vPro / Intel Standard Manageability / DASH V1.1	- / - / -
SATA / ATA / RAID / eSATA-Support / mSATA / M.2 SSD	✓ / - / - / ✓ / - / ✓
FireWire™ / USB 2.0 / USB 3.0	- / ✓ / ✓
FAN monitored & controlled PSU / CPU / AUX1 ²⁾ / AUX2	- / ✓ / ✓ / -
TEMP monitored CPU / onboard sensors / external sensor	✓ / ✓ / -
Special Features	
Silent Fan / Silent Fan LT / System Guard / Silent Drives	✓ / - / ✓ / ✓
Recovery BIOS / Desk Update / Multi Boot	✓ / ✓ / ✓
HDD Password / HDD Encryption / EraseDisk / TPM	✓ / - / ✓ / ✓
Logo Boot Option / Intel On Screen Branding	✓ / ✓
High Efficiency Core Voltage Regulator Design	✓
BIOS POST- / BIOS Boot- / OS- HW Watchdog	✓ / ✓ / ✓
Operating Mode 24-7 / 8-5 (hrs per day - days per week)	✓ / -
Mainboard operating temperature range (chassis inside) ¹⁾	0°C – 60°C
Internal Connectors	
SO DIMM Sockets (DDR4 2133)	2
PCI Express x16 (Gen3) / Support for lane split (8+8 or 8+4+4)	1 / -
mSATA / Mini PCI Express Slot (halfsize / fullsize, incl.USB 2.0)	- / 1
SATA-600 / SATA-300 / mSATA / M.2 SSD ⁴⁾	2 / - / - / 1
S/PDIF (digital Audio) OUT / IN	1 / 0
Frontpanel Audio (9-Pin, HD Audio & Legacy Audio AC97)	1
USB 2.0 channels / USB 3.0 channels / USB Stick (3.0)	2 / 2 / -
Serial (COM2, RS232) / Parallel Port Connector	1 / -
LVDS / LVDS Backlight / Embedded DisplayPort	1 / 1 / 1
FAN PSU / CPU / AUX1 ²⁾ / AUX2	0 / 1 / 1 / 0
Intrusion (Case Open) / GPIO(I/8Bit) / SMBus (Case Temp.)	1 / 1 / -
ATX Power Supply (24 pin + 4 pin) / 12V-only PSU ³⁾	1 / 1
External Connectors	
VGA Sub D / DVI-I / DVI-D / DisplayPort V1.2	- / - / 1 / 1
Audio Mic. In / Line in / Line out (or driver configuration)	- / 1 / 1
LAN (RJ-45)	2
PS/2 Mouse / Keyboard	1 / 1
USB 2.0 / USB 3.0	3 / 2
Serial (COM1, RS232)	1


1) Forced cooling required, see technical documentation for detailed requirements

2) Fan AUX1 = 3Pin & PWM support


3) Alternative: Powered by 12V DC only. See TechNotes document for further details

4) If a M.2 module @60mm is installed, only halfsize Mini-PCIe module can be installed! D3434-S supports M.2 SATA-based modules only!

External Connectors



Connector / Socket Diagram



Further industrial products offered by Fujitsu

- Connectors
- KVM Switches
- Relays
- Touch Panels
- Thermal Printers
- Wireless Modules



24 Volt Kiosk Printers



Multi-Input Touch Panels

Contact:

Fujitsu Components Europe, B.V.
 Tel.: +31 (0)23 556 0910
 Fax: +31 (0)23 556 0950
 Website: emea.fujitsu.com/components
 Address: Diamantlaan 25
 2132 WV Hoofddorp
 Netherlands

More information

Fujitsu products, solutions & services

Products

www.fujitsu.com/global/products/

In addition to the Fujitsu [Product name], Fujitsu offers a full portfolio of other computing products.

Computing products

- Storage systems: ETERNUS
- Server: PRIMERGY, PRIMEQUEST, Fujitsu SPARC M10, BS2000/OSD Mainframe
- Client Computing Devices: LIFEBOOK, STYLISTIC, ESPRIMO, FUTRO, CELSIUS
- Peripherals: Fujitsu Displays, Accessories
- Software
- Network

Product Support Services with different service levels agreements are recommended to safeguard each product and ensure smooth IT operation.

Solutions

<http://www.fujitsu.com/global/solutions>

The Fujitsu solutions combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu's Solutions include parts of one or more activity groups (e.g., planning, implementation, support, management, and training services) and are designed to solve a specific business need.

Infrastructure Solutions are customer offerings created by bringing Fujitsu's best products, services and technologies together with those from partners to deliver benefit to our customers' businesses.

Industry Solutions are tailored to meet the needs of specific verticals.

Business and Technology Solutions provide a variety of technologies developed to tackle specific business issues such as security and sustainability, across many verticals.

Services

www.fujitsu.com/global/services/

Several customizable Fujitsu Service offerings ensure that IT makes a real difference and delivers true business value. We do this by leveraging our extensive experience in managing large, complex, transformational IT programs to help clients in planning, delivering and operating IT services in a challenging and changing business environment.

Application Services support the development, integration, testing, deployment and on-going management of both custom developed and packaged applications. The services focus on delivering business and productivity improvements for organizations.

Business Services respond to the challenge of planning, delivering and operating IT in a complex and changing IT environment.

Managed Infrastructure Services enable customers to deliver the optimal IT environment to meet their needs – achieving high levels of IT service quality and performance for data center and end user environments.

Fujitsu green policy innovation

www.fujitsu.com/global/about/environment/
Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to resolve issues of environmental energy efficiency through IT. Please find further information at:



More information

Learn more about Fujitsu, please contact your Fujitsu sales representative, Fujitsu business partner, or visit our website.
www.fujitsu.com/fts/mainboards/

Copyright

© 2015 Fujitsu Technology Solutions GmbH
Fujitsu and the Fujitsu logo are trademarks or registered trademarks of Fujitsu Limited in Japan and other countries.

Intel® Q87 Express Chipset, Intel® Core™ i7 / i5 / i3, Intel® "TE" Haswell, Intel® Pentium®-G3xxx and Intel® Celeron G18xx are trademarks or a registered trademark of Advanced Micro Devices, Inc. in America and other countries. Other company, product and service names may be trademarks or registered trademarks of their respective owners.

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.

Disclaimer

Technical data subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

FUJITSU Technology Solutions
OEM Mainboard Sales
Email: oem-sales@ts.fujitsu.com

Website: <http://ts.fujitsu.com>
2016-21-01